



Materials: Aluminum Bronze

Tolerances: T; +/- .001; W: +/- .010

With Graphite Plugs

T	Width (W)								Rec. Mounting Screw
	1.5	2	2.5	3	4	5	6	8	
1/4	212-320NG*	216-320NG	220-320NG	224-320NG*	232-320NG				
3/8	312-320NG*	316-320NG*	320-320NG*	324-320NG	332-320NG	340-320NG*	348-320NG*		1/4 SHCS
1/2	412-320NG	416-320NG	420-320NG	424-320NG	432-320NG	440-320NG	448-320NG*	464-320NG*	3/8 SHCS
5/8	512-320NG*	516-320NG*	520-320NG*	524-320NG	532-320NG	540-320NG*	548-320NG*		3/8 SHCS
3/4	612-320NG*	616-320NG*	620-320NG*	624-320NG	632-320NG	640-320NG			1/2 SHCS

Application Note: For standard sizes, Graphite Plugs are on 1" centers to facilitate cutting.
Drill mounting holes either between or through Graphite Plugs.
When going through a plug, first break out the graphite with a center punch and you'll have a pre-spotted hole.

Without Graphite Plugs (Solid Bronze)

T	Width (W)								
	1	1.5	2	2.5	3	4	5	6	8
1/4	28-320N	212-320N	216-320N	220-320N	224-320N	232-320N	240-320N	248-320N	
3/8	38-320N	312-320N	316-320N	320-320N	324-320N	332-320N	340-320N	348-320N	364-320N
1/2	48-320N	412-320N	416-320N	420-320N	424-320N	432-320N	440-320N		
5/8		512-320N*	516-320N*	520-320N*	524-320N*	532-320N*	540-320N*	548-320N*	
3/4	68-320N*	612-320N*	616-320N		624-320N	632-320N	640-320N		

* Special order only

Custom Sizes Are Available!

We welcome custom orders for any size subject to certain size limitations.