



Materials: Base and Gibs: Aluminum Bronze; Slide: 4140 Rc 28-32

Tolerances: +/-0.010 unless otherwise indicated

Catalog Number				W +0.000 -0.005	L -0.005 -0.015	A	D	E	F	G	H	Screws		W1	W2 +0.000 -0.001	H1	H2 +0.000 -0.001	LS	P	
Slide	Assy	L-Gib	Base									No.	Size							
HAS15	HA25	HAL25	HAB25	2.246	2.50	.500	.312	.500	1.124	0.750	.875	4	1/4	1.105	.749	1.00	.312	1.5	.25	
		HA30	HAL30		HAB30							3.00								4
HAS25	HA35	HAL35	HAB35	3.125	3.50	.375	.375	.750	1.625	1.125	.985	4	5/16	1.615	1.124	1.17	.374	2.5	.50	
		HA40	HAL40		HAB40							4.00								6
		HA45	HAL45		HAB45							4.50								6

Ordering Notes:

- Gib Assembly consists of (2) L-Gibs and (1) base plate; order slides separately.
- Use a "D" suffix on the catalog number (e.g. HA40D) to specify pre-assembled with dowels.
- Use a "G" suffix on the catalog number to specify with graphite; a "G" suffix should also be used when ordering the slide.

Application Notes:

- No need for messy drilling and doweling.
- When installed in a close fitting pocket, the sides of the pocket in combination with the slide, locate the L-Gibs and keep them from moving.
- When not installed in a close fitting pocket, order Gib Assemblies pre-assembled with dowels; width tolerance for these is +/-0.005.