



Materials: 4140 flame hardened to Rc 56-62

Tolerances: Screw Holes: +/- .25; Dowel Holes: +/- .10

Catalog Number	NAAMS Code	Holes	L	A	B	C	D	E	F	H
25K75G	R012507	2	75			38	51	25	15	37
25K100G	R012510	2	100			63	76			
25K125G	R012512	3	125		50.5	88	101			
25K150G	R012515	3	150		63	113	126			
25K175G	R012517	3	175		75.5	138	151			
25K200G	R012520	4	200	63	113	163	176			
32K75G	R013207	2	75			38	51	32	15	45
32K100G	R013210	2	100			63	76			
32K125G	R013212	3	125		50.5	88	101			
32K150G	R013215	3	150		63	113	126			
32K175G	R013217	3	175		75.5	138	151			
32K200G	R013220	4	200	63	113	163	176			
37K75G	R013707	2	75			38	51	37	30	50
37K100G	R013710	2	100			63	76			
37K125G	R013712	3	125		50.5	88	101			
37K150G	R013715	3	150		63	113	126			
37K175G	R013717	3	175		75.5	138	151			
37K200G	R013720	4	200	63	113	163	176			
48K75G	R014807	2	75			38	51	48	30	60
48K100G	R014810	2	100			63	76			
48K125G	R014812	3	125		50.5	88	101			
48K150G	R014815	3	150		63	113	126			
48K175G	R014817	3	175		75.5	138	151			
48K200G	R014820	4	200	63	113	163	176			
48K250G	R014825	4	250	83	153	213	226	55	30	75
55K75G	R015507	2	75			38	51			
55K100G	R015510	2	100			63	76			
55K125G	R015512	3	125		50.5	88	101			
55K150G	R015515	3	150		63	113	126			
55K175G	R015517	3	175		75.5	138	151			
55K200G	R015520	4	200	63	113	163	176			
55K250G	R015525	4	250	83	153	213	226			