



Materials: Male: O6 hardened to Rc 60-62 Black Oxide coated; Female: S7 hardened to Rc 50-52 Titanium Nitrided to Rc 80

Catalog Number	W +.0000 -.0004	H +.000 -.005	A	B .0001/.0003 clearance per side	C	D	E +.010 -.010 clearance per side	T	R (pocket radius)	SHCS
MSL100	1.000	2.000	.530	.500	.875	1.125	.250	.375	.187	10-32 x 1/2
MSL125	1.250	2.000	.560	.500	.875	1.125	.250	.490	.187	8-32 x 5/8
MSL150	1.500	1.750	.560	.563	.875	0.875	.250	.500	.187	8-32 x 5/8
MSL200	2.000	2.250	.660	.750	.875	1.375	.312	.500	.250	10-32 x 5/8
MSL300	3.000	2.750	1.130	1.250	.875	1.875	.375	.750	.250	1/4-20 x 3/4
MSL400	4.000	3.750	1.130	1.500	1.375	2.375	.500	1.000	.500	3/8-16 x 1
MSL500	5.000	4.250	1.630	2.000	1.375	2.875	.625	1.250	.500	1/2-13 x 1 1/4
MSL600	6.000	4.250	1.750	2.000	1.375	2.875	.625	1.500	.500	1/2-13 x 1 1/2