



Tolerances	
Pin Diameter (D)	+0.001 -0.000
Head Diameter (H)	+0.000 -0.010
Head Thickness (T)	+0.000 -0.002
Length (L)	+0.030 -0.000

STANDARD HARDNESS Rc 30 - 35					
D Pin Dia	H Head Dia	T Head Thick	Catalog Number		
			L = 3	L = 6	L = 10
3/32	1/4	1/8	CPS09L03	CPS09L06	CPS09L10
7/64	1/4	1/8	CPS10L03	CPS10L06	CPS10L10
1/8	1/4	1/8	CPS12L03	CPS12L06	CPS12L10
9/64	1/4	1/8	CPS14L03	CPS14L06	CPS14L10
5/32	9/32	5/32	CPS15L03	CPS15L06	CPS15L10
11/64	11/32	3/16	CPS17L03	CPS17L06	CPS17L10
3/16	3/8	3/16	CPS18L03	CPS18L06	CPS18L10
13/64	3/8	3/16	CPS20L03	CPS20L06	CPS20L10
7/32	13/32	3/16	CPS21L03	CPS21L06	CPS21L10
1/4	7/16	3/16	CPS25L03	CPS25L06	CPS25L10
9/32	7/16	1/4	CPS28L03	CPS28L06	CPS28L10
5/16	1/2	1/4	CPS31L03	CPS31L06	CPS31L10
11/32	9/16	1/4	CPS34L03	CPS34L06	CPS34L10
3/8	5/8	1/4	CPS37L03	CPS37L06	CPS37L10
13/32	11/16	1/4	CPS40L03	CPS40L06	CPS40L10
7/16	11/16	1/4	CPS43L03	CPS43L06	CPS43L10
15/32	3/4	1/4	CPS46L03	CPS46L06	CPS46L10
1/2	3/4	1/4	CPS50L03	CPS50L06	CPS50L10
9/16	13/16	1/4		CPS56L06	CPS56L10
5/8	7/8	1/4		CPS62L06	CPS62L10
3/4	1	1/4		CPS75L06	CPS75L10

HIGH HARDNESS Rc 50 - 55					
D Pin Dia	H Head Dia	T Head Thick	Catalog Number		
			L = 3	L = 6	L = 10
3/32	1/4	1/8	CPH09L03	CPH09L06	CPH09L10
7/64	1/4	1/8	CPH10L03	CPH10L06	CPH10L10
1/8	1/4	1/8	CPH12L03	CPH12L06	CPH12L10
9/64	1/4	1/8	CPH14L03	CPH14L06	CPH14L10
5/32	9/32	5/32	CPH15L03	CPH15L06	CPH15L10
11/64	11/32	3/16	CPH17L03	CPH17L06	CPH17L10
3/16	3/8	3/16	CPH18L03	CPH18L06	CPH18L10
13/64	3/8	3/16	CPH20L03	CPH20L06	CPH20L10
7/32	13/32	3/16	CPH21L03	CPH21L06	CPH21L10
1/4	7/16	3/16	CPH25L03	CPH25L06	CPH25L10
9/32	7/16	1/4	CPH28L03	CPH28L06	CPH28L10
5/16	1/2	1/4	CPH31L03	CPH31L06	CPH31L10
11/32	9/16	1/4	CPH34L03	CPH34L06	CPH34L10
3/8	5/8	1/4	CPH37L03	CPH37L06	CPH37L10
13/32	11/16	1/4	CPH40L03	CPH40L06	CPH40L10
7/16	11/16	1/4	CPH43L03	CPH43L06	CPH43L10
15/32	3/4	1/4	CPH46L03	CPH46L06	CPH46L10
1/2	3/4	1/4	CPH50L03	CPH50L06	CPH50L10
9/16	13/16	1/4		CPH56L06	CPH56L10
5/8	7/8	1/4		CPH62L06	CPH62L10
3/4	1	1/4		CPH75L06	CPH75L10