



Materials: SAE 4140

Tolerances: +/- .010

Catalog Number	L	W	N	D	S	A	B	C	E	F		
KPSG10408*	8.00	4.00	3		2.12	1.50	4.00			6.50		
KPSG10410*	10.00								3.25	5.00	6.75	8.50
KPSG10412*	12.00								3.75	6.00	8.25	10.50
KPSG10414*	14.00						5	4.25	7.00	9.75	12.50	
KPSG10416*	16.00							4.75	8.00	11.25	14.50	
KPSG10418*	18.00							5.25	9.00	12.75	16.50	
KPSG10508*	8.00	5.00	3	2.25	3.12	1.00	4.00			7.00		
KPSG10510*	10.00								3.00	5.00	7.00	9.00
KPSG10512*	12.00								3.50	6.00	8.50	11.00
KPSG10514*	14.00						5	4.00	7.00	10.00	13.00	
KPSG10516*	16.00							4.50	8.00	11.50	15.00	
KPSG10518*	18.00							5.00	9.00	13.00	17.00	
KPSG10608*	8.00	6.00	4	3.25	4.12	1.00	2.25		5.75	7.00		
KPSG10610*	10.00								3.00	5.00	7.00	9.00
KPSG10612*	12.00								3.50	6.00	8.50	11.00
KPSG10614*	14.00						5	4.00	7.00	10.00	13.00	
KPSG10616*	16.00							4.50	8.00	11.50	15.00	
KPSG10618*	18.00							5.00	9.00	13.00	17.00	

*Suffix: D - for double wear plates (N/A on 4" widths)
S - for single wear plates
N - for no screw holes

Examples: KPSG10508D
KPSG10512N