



**Materials:** 4140 flame hardened to Rc 56-62

**Tolerances:** Screw Holes: +/- .25; Dowel Holes: +/- .10

Catalog Number	NAAMS Number	Holes	L	A	B	C	D	E	F	H	J	W
40G75G	G014007	2	75			38	51	18	33	40	15	
40G100G	G014010	2	100			63	76					
40G125G	G014012	3	125		50.5	88	101					
40G150G	G014015	3	150		63	113	126					
40G175G	G014017	3	175		75.5	138	151					
40G200G	G014020	4	200	63	113	163	176					
40G225G	G014022	4	225	73	128	188	201					
40G250G	G014025	4	250	83	153	213	226					
45G75G	G014507	2	75			38	51					
45G100G	G014510	2	100			63	76					
45G125G	G014512	3	125		50.5	88	101					
45G150G	G014515	3	150		63	113	126					
45G175G	G014517	3	175		75.5	138	151					
45G200G	G014520	4	200	63	113	163	176					
45G225G	G014522	4	225	73	128	188	201					
45G250G	G014525	4	250	83	153	213	226					
50G75G	G015007	2	75			38	51					
50G100G	G015010	2	100			63	76					
50G125G	G015012	3	125		50.5	88	101					
50G150G	G015015	3	150		63	113	126					
50G175G	G015017	3	175		75.5	138	151					
50G200G	G015020	4	200	63	113	163	176					
50G225G	G015022	4	225	73	128	188	201					
50G250G	G015025	4	250	83	153	213	226					
60G75G	G016007	2	75			38	51					
60G100G	G016010	2	100			63	76					
60G125G	G016012	3	125		50.5	88	101					
60G150G	G016015	3	150		63	113	126					
60G175G	G016017	3	175		75.5	138	151					
60G200G	G016020	4	200	63	113	163	176					
60G225G	G016022	4	225	73	128	188	201					
60G250G	G016025	4	250	83	153	213	226					
75G75G	G017507	2	75			38	51					
75G100G	G017510	2	100			63	76					
75G125G	G017512	3	125		50.5	88	101					
75G150G	G017515	3	150		63	113	126					
75G175G	G017517	3	175		75.5	138	151					
75G200G	G017520	4	200	63	113	163	176					
75G225G	G017522	4	225	73	128	188	201					
75G250G	G017525	4	250	83	153	213	226					