



**Materials:** 1.2344 (H-13)

**Hardness:** Core: 40 - 44 Rc; Surface: 68-72 Rc

Prefix	D g6	H +0/-0.02	T +0/-0.05	Available Lengths										
				100	125	160	200	250	315	400	500	630	800	1000
EM1.5-	1.5	3	1.5	.	.	.	.							
EM2-	2	4	2	.	.	.	.	.	.	.				
EM2.2-	2.2			.	.	.	.	.	.					
EM2.5-	2.5	5	2	.	.	.	.	.	.					
EM2.7-	2.7			.	.	.	.	.	.					
EM3-	3	6	3	.	.	.	.	.	.	.	.	.	.	.
EM3.2-	3.2			.	.	.	.	.	.	.	.	.	.	.
EM3.5-	3.5	7	3	.	.	.	.	.	.	.	.	.	.	.
EM3.7-	3.7			.	.	.	.	.	.	.	.	.	.	.
EM4-	4	8	3	.	.	.	.	.	.	.	.	.	.	.
EM4.2-	4.2			.	.	.	.	.	.	.	.	.	.	.
EM4.5-	4.5	10	3	.	.	.	.	.	.	.	.	.	.	.
EM5-	5			.	.	.	.	.	.	.	.	.	.	.
EM5.2-	5.2	10	3	.	.	.	.	.	.	.	.	.	.	.
EM5.5-	5.5			.	.	.	.	.	.	.	.	.	.	.
EM6-	6	12	5	.	.	.	.	.	.	.	.	.	.	.
EM6.2-	6.2			.	.	.	.	.	.	.	.	.	.	.
EM6.5-	6.5	14	5	.	.	.	.	.	.	.	.	.	.	.
EM7-	7			.	.	.	.	.	.	.	.	.	.	.
EM8-	8	14	5	.	.	.	.	.	.	.	.	.	.	.
EM8.2-	8.2			.	.	.	.	.	.	.	.	.	.	.
EM8.5-	8.5	16	5	.	.	.	.	.	.	.	.	.	.	.
EM9-	9			.	.	.	.	.	.	.	.	.	.	.
EM10-	10	16	5	.	.	.	.	.	.	.	.	.	.	.
EM10.2-	10.2			.	.	.	.	.	.	.	.	.	.	.
EM10.5-	10.5	20	7	.	.	.	.	.	.	.	.	.	.	.
EM11-	11			.	.	.	.	.	.	.	.	.	.	.
EM12-	12	20	7	.	.	.	.	.	.	.	.	.	.	.
EM12.2-	12.2			.	.	.	.	.	.	.	.	.	.	.
EM12.5-	12.5	22	7	.	.	.	.	.	.	.	.	.	.	.
EM14-	14			.	.	.	.	.	.	.	.	.	.	.
EM16-	16	24	7	.	.	.	.	.	.	.	.	.	.	.
EM18-	18			.	.	.	.	.	.	.	.	.	.	.
EM20-	20	26	8	.	.	.	.	.	.	.	.	.	.	.
EM25-	25	32	10	.	.	.	.	.	.	.	.	.	.	.
EM32-	32	40		.	.	.	.	.	.	.	.	.	.	.

**Ordering Information:** Catalog number is prefix plus length (e.g., EM5.5-200).